

WireXpert
500

CERTIFICATION



CABLE TESTER OF CHOICE

WireXpert 500 is the most affordable copper cable certification tester for twisted pair cabling systems with performance levels up to CAT6A/Class E_A. Electricians and network cabling contractors can perform certification testing on copper installations with speed and accuracy using WireXpert 500. In addition to standards based permanent link and channel certification, WireXpert 500 offers optional test adapters for coaxial cable testing and patchcord testing.



Key Features

- Advanced cable certification up to 500 MHz
- Certifies to Industry standards – Class D/E/E_A & Category 5e/6/6A
- Fast Autotest time of 9 seconds
- Meets TIA and ISO Level III accuracy requirements
- Certification testing of Patch-cords
- Industrial Ethernet testing with M12 connectivity
- Advanced reporting and documentation
- Most affordable certifier for premise cabling and industrial Ethernet

Easy to Use and ruggedized design

WireXpert 500 comes with an intuitive touch sensitive user interface, featuring bright colour LCD screens designed for industrial, heavy duty usage. The Dual Control System (DCS™) – featuring identical devices for remote and main unit – makes it fast and simple to operate the test cycles. Whether used by two technicians or one person working alone, walking time between outlets is minimized.

Fast and simple for highest productivity

WireXpert 500 completes CAT 6A certification test in seconds. It offers intuitive navigation through the on screen menus, and generates professional reports through the accompanying ReportXpert PC software.

Proven Accuracy

WireXpert 500 is based on measurement system independently verified by highly respected test laboratories including ETL.

Kit Includes	Quantity
WireXpert 500 H	2
L-I B	2
C	2
D P C	2
CA 6A P L A	2
CA 6A P L A	2
CA 6A C A	2
B D	1
M	
A H	2
AC P A	2
C P C	2
C C	1
C C	1
Q A G	1

WireXpert 500 offers an efficient way for quickly identifying and recording the performance of patch-cords. With its fast and accurate dual-ended testing, WireXpert 500 patch-cord test kits are suitable for both manufacturing test applications, as well as for incoming inventory inspection at end user premises. WireXpert 500 patch-cord test kits are available for testing CAT5e, CAT6, and CAT6A patch-cords.

The WireXpert 500 industrial Ethernet cable test solution comprise of M12 adapter kits with both channel and permanent link configurations using M12 industrial Ethernet connectors are supported. Industrial Ethernet kits supporting X-Coded M12 interface are also available, making it possible to effectively test 10-Gig ready industrial Ethernet cables.

WireXpert 500 also supports testing of coaxial cables for attenuation and return loss with the optional coax test adapters.

Adapters & Accessories for Copper Cable Certification

Adapters & Accessories	
C	E _A / CA 6A
C	EA / CA 6A
P	
P	CA 6A
H	
P	
F	P

Manage your results and generate professional reports and warranty documents. The WireXpert 500 certification solution includes ReportXpert, a PC based reporting software utility that produces full colour graphical reports in summary or detail.



PSIBER DATA OFFICES

AMERICAS

Psiber Data Systems Inc.,
San Diego, USA
Phone: +1 (619) 287 9970
info@psiber.com

ASIA / PACIFIC

Psiber Data Pte Ltd, Singapore
Phone: +65 6569 6019
asiasales@psiber-data.com

EUROPE / M. EAST / AFRICA

Psiber Data GmbH
Munich, Germany
Phone: +49 (89) 8913 6060
info@psiber-data.com

FRANCE

Psiber Data France,
Paris, France
Phone: +33 (660) 970910
info@psiber-data.com

GERMANY

Psiber Data GmbH
Munich, Germany
Phone: +49 (89) 8913 6060
info@psiber-data.com

ITALY

Psiber Italia, Monza,
Milano, Italy
Phone: +39 (039) 284 4287
info@psiber.it

UNITED KINGDOM

Psiber Data Ltd.,
Faygate, UK
Phone: +44 (1293) 852 306
info@psiber-data.co.uk

www.psiberdata.com

For more information please contact:



Performance	
Certification	
Certification Testing	TIA 568-C.2 CAT 5e, 6, 6A
	ISO/IEC 11801, EN 50173 Class D,E,E _A
	CAT 5e, 6, and 6A patch-cord
Autotest time - CAT6A	9 sec
Max cable length for dual ended Autotest	500m
Insertion Cycles	Channel: 10,000 typical
	Permanent link: 5,000 typical
TEST PARAMETERS	As specified in TIA 1152, IEC 61935-1
Wiremap	
Loop Resistance	0 to 40 Ω, ±0.1 Ω
Length	0 to 500m, ±0.5m (dual ended testing)
Propagation Delay and Delay Skew	0 to 5000 ns, ±1 ns
Attenuation	0 to 70 dB, ±0.1dB
Pair-to-Pair and Power-Sum NEXT	0 to 85 dB, ±0.2 dB
Pair-to-Pair and Power-Sum ACRF	0 to 85 dB, ±0.2 dB
Return Loss	0 to 40 dB, ±0.2 dB
ACRN, PSACRN	-25 to 85 dB, ±0.5 dB
Advanced Diagnostics	Time-domain fault Locator for RL and NEXT
Measurement Accuracy	exceeds TIA 1152 & IEC61935-1 level IIIe
Measurement Frequency Range	1- 500 MHz
General Features	
Interfaces	Probe Interface, RJ-45 Ethernet, USB host and device, talkset, power jack
Display	6" industrial LCD, touch sensitive area on both units
Enclosure	Ruggedized plastic with rubber overmould, withstands 1.5m drop test on hard surface
Remote unit abilities	View test results, save tests, start autotest
Power Supply	AC 100-240V to 12V, 3A power adapter
Input over-voltage protection	Protected against Telco voltages
Battery	Removable and rechargeable Li-Ion
Battery Capacity	>8 hours continuous operation
Internal Storage Capacity	2000 copper test results with full plot information
External Storage	USB Flash Drive
Dimensions	232 X 126 X 87 mm (9.1 X 5.0 X 3.4 inch)
Weight	Approx. 1.4 kg (3.0 lb) / unit
Supported Languages	Chinese, Czech, English, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Calibration period	1 year
Environmental	
Operating Temperature	0 to 40°C
Storage Temperature	-20 to 60°C
Relative humidity	10% to 80%