

BRAIDED SLEEVINGS | BLACK & GREY

INSULATED SLEEVINGS



DESCRIPTION:

Braided sleeving is lightweight self-fitting, self-extinguishing, flexible sleeving that provides tough protection for bundles, wires, cables and flexible pipe systems. Suitable for use with cables up to a maximum diameter of 140mm, it has excellent ageing characteristics. Extremely useful for cable harnessing because of its high elasticity and flexibility. It is low smoke, low toxicity and halogen-free. Available in black or grey as standard. Other colours are available on request; red, blue, yellow, orange, brown, green, white, clear, purple striped and custom patterns. Minimum order quantities may apply.

APPLICATIONS:

Ideal for use in automotive, control panel installation, rail traction and rolling stock, aerospace, military vehicles, submarines, ships and data telecommunications.

SPECIFICATION:

COLOUR OPTIONS:	Black or Grey as standard. Other colours available MOQ may apply.		
MATERIAL:	Self-extinguishing, Heat Stabilised Polyester		
MONOFILAMENT:	Polyester Size 0.22mm		
MELTING POINT:	+250°C	LIMITING OXYGEN INDEX:	34%
CONTINUOUS TEMPERATURE:	50°C to +150°C	MAXIMUM WORKING TEMPERATURE:	+250°C
FLAME RESISTANCE:	Passes Flame Requirement of CEI 332-1, FMVSS 302 (Type A) 12 According to NF F 16-101		
FUMES TOXICITY/OPACITY:	Passes CEI 754-1, CE 754/2, Low Smoke, NFC20452 (Polymer)		
CHEMICAL RESISTANCE:	Unaffected by most chemicals.		



PART NUMBERS:

PART NO. BLACK	BVP CODE	PART NO. GREY	BVP CODE	MIN DIA. (MM)	MAX DIA. (MM)	BOX QTY (M)
C 6TS/6-B	PB 6	C 6TS/6-G	PG 6	5	9	100
C 6TS/8-B	PB 8	C 6TS/8-G	PG 8	6	12	100
C 6TS/10-B	PB 10	C 6TS/10-G	PG 10	8	14	100
C 6TS/12-B	PB 12	C 6TS/12-G	PG 12	10	16	50
C 6TS/15-B	PB 15	C 6TS/15-G	PG 15	12	20	50
C 6TS/20-B	PB 20	C 6TS/20-G	PG 20	18	25	50
C 6TS/25-B	PB 25	C 6TS/25-G	PG 25	22	30	25
C 6TS/30-B	PB 30	C 6TS/30-G	PG 30	26	35	25
C 6TS/40-B	PB 40	C 6TS/40-G	PG 40	35	45	25
C 6TS/50-B	PB 50	C 6TS/50-G	PG 50	45	55	25
C 6TS/60-B	PB 60	C 6TS/60-G	PG 60	65	88	25
C 6TS/75-B	PB 75	C 6TS/75-G	PG 75	70	108	25
C 6TS/100-B	PB 100	C 6TS/100-G	PG 100	95	140	25

